




<b>Single-band Panel</b>	<b>806~896</b>
<b>Dual Polarization</b>	<b>X</b>
<b>Half-power Beam Width</b>	<b>90°</b>
<b>Variable Electrical Downtilt</b>	<b>0°-8°</b>

**XPo1 806~896MHz 90° 16dBi 0° -8° Tilt**

<b>Electrical specifications</b>	<b>KBT90DP16-08AE</b>
Frequency range (MHz)	806~896
Polarization	±45°
Gain (dBi)	2×16
Electrical Downtilt (°)	0~8
Half-power beam width (°)	Horizontal:90 Vertical:8
Sidelobe suppression for first sidelobe above main beam (dB)	0°...4°...8° 16...16...15
Front-to-back ratio (dB)	≥23
Cross-polar discrimination (dB)	≥15(±60°≥10)
Isolation (dB)	≥30
Impedance (Ω)	50
VSWR	≤1.5
Intermodulation IM3 (2×43dBm carrier)	≤-150dBc
Maximum power (W)	400
Lighting protection	DC Ground



<b>Mechanical specifications</b>	
Connector	2×7/16DIN Female
Connector position	Bottom
Height/width/depth (mm)	2530×270×137
Packing size (mm)	2780×360×230
Weight (kg)	21
Radome material	UPVC
Radome color	Gray
Mechanical tilt (°)	0~10
Operating temperature (°C)	-40~60
Rated wind velocity (m/s)	60
Suitable pole diameter (mm)	50~115
Mounting kit	JM-900BZ
Electrical downtilt adjustment	Manual or by optional RCU



**806~896MHz: ±45° Polarization**

